

C1448 - 1400lb Cube Ice Machine

Prodigy Plus® Modular Cube Ice Machine

The world's smartest cuber.

As the world's only self-monitoring cuber, the new Scotsman Prodigy Plus® cube ice machines make it easier than ever to maintain your equipment and save money. Whether it's the advanced ice level control or an optional feature board for quick diagnostics, this is ice-making re-imagined. And with intuitive technology like AutoAlert™ indicator lights, a reduced operational footprint and easy-access service from the front panel, Prodigy Plus® cubers are simply the smartest, most reliable way to create fresh-tasting ice — every time.



The Prodigy Plus® difference. • AutoAlert™ indicator lights for better visibility

- Operational footprint among the industry's smallest
- Industry-exclusive QR code instantly connects users to service information and warranty history
- One-touch cleaning reduces labor costs and saves time
- Front-located air filter for more efficient operation
- Self-aligning front panel for easy access to key components
- Patented WaterSense purge control automatically reduces scale buildup
- Patented Harvest Assist efficiently moves cube ice to the bin
- Smart-Board™ advanced feature module available for additional diagnostic
- Optional Vari-Smart™ ice level control allows operators to customize ice levels
- Antimicrobial protection guards internal surfaces between cleanings
- A full range of water- and energy-saving features



24 Hour Volume Production

Air Cooled			Remote			Wat	Water Cooled		
70°F/21°C 50°F/10°C	Air Water	90°F/32°C 70°F/21°C	70°F/21°C 50°F/10°C	Air Water	90°F/32°C 70°F/21°C	70°F/21°C 50°F/10°C	Air Water	90°F/32°C 70°F/21°C	
1553/706 lb/kg		1296/589 lb/kg	1357/617 lb/kg		1258/572 lb/kg	1444/656 lb/kg		1340/609 lb/kg	



B948S



Modular Bin Options

Model Number*	Dimensions W" x D" x H"	Bin Application Capacity lb/kg	Finish	Ship Weight lb/kg
B948S	48 x 34 x 44**	893/406	Metallic	209/95
BH1100BB	48 x 34 x 50**	1100/499	SS w/ GBB†	280/127
BH1100SS	48 x 34 x 50**	1100/499	Stainless Steel	280/127
BH1300BB	60 x 34 x 50**	1400/635	SS w/ GBB†	310/141
BH1300SS	60 x 34 x 50**	1400/635	Stainless Steel	310/141

- * Contact Scotsman for bin top requirements. ** Add 6" Height for bin legs
- † Stainless steel with galvanized back & bottom.



BH1100BB BH1100SS



BH1300BB BH1300SS








- 3 years parts and labor on all components.
- 5 years parts and labor on the evaporator.
- 5 years parts on the compressor and condenser.
- Warranty valid in North, South & Central America for commercial installations.
- · Contact factory for warranty in other regions.
- · Residential Applications: 1 year parts and labor



• 101 Corporate Woods Parkway, Vernon Hills, IL 60061 •

C1448 - 1400lb Cube Ice Machine

Prodigy Plus® Modular Cube Ice Machine



Specifications

	Model Number* Cube Size: medium or small	Condenser Unit	Basic Electrical Volts/Hz/Phase	Max. Fuse Size or HACR Circuit Breaker (amps)	Circuit Wires	Min. Circuit Ampacity	Energy Consumption kWh/100 lb (45.4 kg) 90°F(32°C)/70°F(21°C)	Potable	b (liters/45.4 kg Condenser)/70°F(21°C)) Energy Star®
	C1448MA-32 C1448MA-3 C1448MR-32 C1448MR-3 C1448MW-32 C1448MW-3	Air Air Remote Remote Water Water	208-230/60/1 208-230/60/3 208-230/60/1 208-230/60/3 208-230/60/1 208-230/60/3	30 30 30 30 30 30	2 3 2 3 2 3	17.7 13.6 17.0 12.9 16.0 11.9	4.25 4.25 4.34 4.34 3.70 3.70	18.0/68.3 18.0/68.3 18.0/68.3 18.0/68.3 18.0/68.3 18.0/68.3	- - - 100.0/379.5 100.0/379.5	*
Siii.	C1448SA-32 C1448SA-3 C1448SR-32 C1448SR-3 C1448SW-32 C1448SW-3	Air Air Remote Remote Water Water	208-230/60/1 208-230/60/3 208-230/60/1 208-230/60/3 208-230/60/1 208-230/60/3	30 30 30 30 30 30	2 3 2 3 2 3	17.7 13.6 17.0 12.9 16.0 11.9	4.25 4.25 4.34 4.34 3.70 3.70	18.0/68.3 18.0/68.3 18.0/68.3 18.0/68.3 18.0/68.3 18.0/68.3	- - - - 100.0/379.5 100.0/379.5	*



All Models

Dimensions	(W)	(D	х	H):
------------	-----	-----	---	-----

Unit: 48" x 24" x 29"

(121.9 x 61.0 x 73.7 cm)

Shipping Carton: 52" x 27" x 35"

52" x 27" x 35" (132.1 x 68.6 x 88.9 cm)

Shipping Weight: BTUs per hour: 345 lb / 157 kg 20,000

Refrigerant: R-404A



Accessories

Model Number	Description
KVS	Vari-Smart™ Ice Level Control - Program ice bin levels to match ice needs.
KSBU	Smart-Board™ Advanced Control - Use additional operational data for fast diagnosis.
KSBU-N	Smart-Board™ Advanced Control with Network - Network capable.
ERC311-32	Remote condenser for C1448xR, 208-230/60/1 - Consult remote condenser spec sheet for details
BRTE10	10ft (3.0 m) line set, brazing required
BRTE25	25ft (7.6 m) line set, brazing required
BRTE40	40ft (12.2 m) line set, brazing required
BRTE75	75ft (22.9 m) line set, brazing required
KPAS	Prodigy Advanced Sustainability Kit - Includes KVS and KSBU - N

Scotsman recommends all ice machines have water filtration. See Scotsman water filter specification sheet for details.



Operating Requirements

	Minimum	Maximum	
Air Temperatures	50°F (10°C)	100°F (38°C)	
Water Temperatures	40°F (4.4°C)	100°F (38°C)	
Remote Cond. Temps	-20°F (-29°C)	120°F (49°C)	
Water Pressures	20 PSIG (1.4 bar)	80 PSIG (5.5 bar)	
Electrical Voltage	-5%	+10%	

Specifications and design are subject to change without notice





Water Usage