

Bulletin Number: PS - 3 - 2011

Bulletin Date: May 2011

# SERVICE BULLETIN

## Subject: Model Series Revision, C0530 "C" Series

C0530 modular cubers have been changed. The changes are to the compressor, TXV and to the controller. To identify units with these changes, the model series has been changed to  $\bf C$ .

### C Series Service Compressors:

- 115/60/1 18-8948-21 includes starting components
- 208-230/60/1 18-8948-23 includes starting components
- 230/50/1 18-8948-22 includes starting components

Application: Compressors are not interchangeable with prior models. 18-8948-21 also used on MDT5 models, and ships with start relay and start capacitor for the MDT5, not used on C0530C.

## C Series Electrical Ratings have changed (115 volt models listed here):

Model	Minimum Circuit Ampacity	Maximum Fuse Size
C0530SA-1C	15.2	20
C0530SW-1C	13.5	15
C0530SR-1C	16.2	20

#### C Series TXV

• 16-1184-01

Application: This TXV is to be used on C0530 C series.

#### C Series Service Controller

• 11-0550-28 - for all Prodigy cubers.

Application: Do NOT use prior controllers on a C0530C series. Controller 11-0550-27 can be used on all other Prodigy cubers.

#### Other changes

- The Air cooled refrigerant charge for the C series is 21 ounces, prior series charge was 22 ounces. Water and Remote charges did not change.
- Prodigy cuber B & higher series and flaker/nugget top panels are being changed to remove the side trim strips.