

Model Number	Capacity and Energy Input Ratings				Water Use, gal/100# (l/kg)		Cubes per cycle	Amps		CA Power Tier	Dimensions - inches (cm)			Ship Weight
	Lb (Kg) per 24hr 90/70 Ambient/Water	kWh/100# (kJ/kg)	Lb (Kg) per 24hr	kWh/100# (kJ/kg)	Potable	Condenser		Min Circuit	Max Fuse/Breaker		W	D	H	Ship Weight #(kg)
			70/50 Ambient/Water											
GT361AC	216 (98)	7.95 (631)	270 (122.47)	5.96 (473)	22 (1.84)	n/a	63	12	15	1	30.1 (76.5)	25.7 (65.3)	16.9 (42.9)	180 (82)
GT361AHK	255 (116)	7.31 (581)	332 (150.59)	5.12 (406)	23.6 (1.97)	n/a	126	12	15	1	30.1 (76.5)	25.7 (65.3)	16.9 (42.9)	180 (82)
GT361LC	262 (119)	5.56 (441)	309 (140.16)	4.56 (362)	22.2 (1.85)	165.3 (13.79)	63	11.1	15	2	30.1 (76.5)	25.7 (65.3)	16.9 (42.9)	174 (79)
GT361LHK	316 (143)	5.18 (411)	373 (169.19)	4.25 (337)	22.9 (1.91)	180.7 (15.08)	126	11.1	15	2	30.1 (76.5)	25.7 (65.3)	16.9 (42.9)	174 (79)
GT364AC	215 (97)	7.57 (601)	269 (122.01)	5.68 (450)	22.1 (1.8)	n/a	63	6.5	15	2	30.1 (76.5)	25.7 (65.3)	16.9 (42.9)	180 (82)
GT364AHK	255 (116)	6.91 (548)	332 (150.59)	4.84 (384)	23.6 (1.97)	n/a	126	6.5	15	2	30.1 (76.5)	25.7 (65.3)	16.9 (42.9)	180 (82)
GT364LC	255 (115)	5.76 (457)	301 (136.53)	4.72 (374)	22 (1.8)	163.4 (13.63)	63	6	15	1	30.1 (76.5)	25.7 (65.3)	16.9 (42.9)	174 (79)
GT364LHK	303 (137)	5.34 (424)	358 (162.38)	4.38 (347)	23.2 (1.94)	188.5 (15.73)	126	6	15	2	30.1 (76.5)	25.7 (65.3)	16.9 (42.9)	174 (79)
GT561AC	369 (167.22)	6.63 (526)	458 (207.74)	5.04 (400)	16.6 (1.39)	n/a	108	18.6	30	1	30.1 (76.5)	25.7 (65.3)	30.7 (78)	228 (103)
GT561AHK	453 (205.44)	6.19 (491)	575 (260.81)	4.52 (358)	20.4 (1.7)	n/a	216	18.6	30	1	30.1 (76.5)	25.7 (65.3)	30.7 (78)	228 (103)
GT561LC	447 (202.56)	5.15 (408)	510 (231.33)	4.43 (351)	13.2 (1.1)	137.4 (11.47)	108	17.7	30	1	30.1 (76.5)	25.7 (65.3)	30.7 (78)	218 (99)
GT561LHK	500 (226.89)	4.85 (384)	580 (263.08)	4.07 (323)	17.1 (1.43)	175.9 (14.68)	216	17.7	30	1	30.1 (76.5)	25.7 (65.3)	30.7 (78)	218 (99)
GT564AC	380 (172.19)	6.88 (545)	471 (213.64)	5.23 (415)	16.7 (1.39)	n/a	108	9.5	15	1	30.1 (76.5)	25.7 (65.3)	30.7 (78)	228 (103)
GT564AHK	433 (196.49)	5.99 (475)	550 (249.47)	4.37 (346)	18.4 (1.54)	n/a	216	9.5	15	1	30.1 (76.5)	25.7 (65.3)	30.7 (78)	228 (103)
GT564LC	429 (194.43)	5.14 (407)	489 (221.80)	4.42 (350)	16.9 (1.41)	175.6 (14.65)	108	9.1	15	1	30.1 (76.5)	25.7 (65.3)	30.7 (78)	218 (99)
GT564LHK	494 (224.26)	4.73 (375)	573 (259.90)	3.97 (315)	15.9 (1.33)	144.2 (12.03)	216	9.1	15	1	30.1 (76.5)	25.7 (65.3)	30.7 (78)	218 (99)
GB561AC	360 (163)	7.1 (563)	446 (202.30)	5.40 (428)	25 (2.1)	n/a	108	18.6	30	1	42.3 (107.4)	31.1 (79)	17 (43.2)	207 (94)
GB561AHK	428 (194)	6.6 (524)	544 (246.75)	4.82 (382)	25 (2.1)	n/a	216	18.6	30	1	42.3 (107.4)	31.1 (79)	17 (43.2)	207 (94)
GB561LC	420 (190)	5.5 (437)	479 (217.27)	4.73 (375)	25 (2.1)	142 (11.9)	108	17.7	30	1	42.3 (107.4)	25.63 (65.1)	17 (43.2)	185 (84)
GB561LHK	500 (227)	5.0 (397)	580 (263.08)	4.20 (333)	25 (2.1)	148 (12.4)	216	17.7	30	1	42.3 (107.4)	25.63 (65.1)	17 (43.2)	185 (84)
GB564AC	357 (162)	7.2 (571)	443 (200.94)	5.47 (434)	25 (2.1)	n/a	108	9.5	15	1	42.3 (107.4)	31.1 (79)	17 (43.2)	207 (94)
GB564AHK	424 (192)	6.5 (516)	538 (244.03)	4.75 (377)	25 (2.1)	n/a	216	9.5	15	1	42.3 (107.4)	31.1 (79)	17 (43.2)	207 (94)
GB564LC	460 (209)	5.2 (413)	524 (237.68)	4.47 (354)	25 (2.1)	150 (12.5)	108	9.1	15	1	42.3 (107.4)	25.63 (65.1)	17 (43.2)	185 (84)
GB564LHK	460 (209)	5.2 (413)	534 (242.21)	4.37 (346)	25 (2.1)	165 (13.8)	216	9.1	15	1	42.3 (107.4)	25.63 (65.1)	17 (43.2)	185 (84)
GB1064AC	725 (329)	6.1 (484)	906 (411)	4.58 (363)	23 (1.9)	n/a	216	16.3	25	1	42.3 (107.4)	31.1 (79)	33.7 (85.6)	348 (158)
GB1064AHK	823 (373)	5.6 (445)	1045 (474)	4.09 (324)	26.5 (2.2)	n/a	432	16.3	25	1	42.3 (107.4)	25.7 (65.3)	33.7 (85.6)	312 (142)
GB1064LC	835 (379)	4.46 (354)	952 (432)	3.84 (304)	16.1 (1.34)	141.8 (11.83)	216	15.4	25	1	42.3 (107.4)	25.7 (65.3)	33.7 (85.6)	312 (142)
GB1064LHK	900 (408)	4.6 (365)	1044 (473)	3.86 (306)	24 (2.0)	163 (13.6)	432	15.4	25	1	42.3 (107.4)	25.7 (65.3)	33.7 (85.6)	312 (142)
GB1064RC & RC214APV	760 (345)	5.9 (468)	950 (431)	4.43 (351)	25 (2.1)	n/a	216	18.1	30	1	42.3 (107.4)	25.7 (65.3)	33.7 (85.6)	335 (152)
GB1064RHK & RC214APV	850 (386)	5.6 (444)	1080 (490)	4.09 (324)	25 (2.1)	n/a	432	18.1	30	1	42.3 (107.4)	25.7 (65.3)	33.7 (85.6)	335 (152)