

# MDT4F12 – TouchFree<sup>®</sup> Ice Machine / Dispenser

## Flake Ice Machine / Dispenser



### Features

Makes and dispenses flaked ice.

Sleek, european design with attractive rounded corners and informative instruction labels.

Up to 25% less fan noise allows installation of the unit in the quietest hallways.

Improved dispensing with easier access and room for most containers.

TouchFree<sup>®</sup> actuation provides convenient one-hand operations and eliminates the risk of cross contamination.

Flexible utility location.

### 24 Hour Volume Production

Air Cooled		
70°F/21°C 50°F/10°C lb/kg	Air Water	90°F/32°C 70°F/21°C lb/kg
453/205		351/159

### Flake Ice



Cools more quickly than other ice forms. Ideal for healthcare.



### Water / Ice Selection Switch



Select ice only or ice and water at the touch of a switch, conveniently located on the front panel.

### Warranty

- 2 years parts and labor on all components.
- 5 years parts on compressor.

Warranty valid in North, South & Central America. Contact factory for warranty in other regions.

### Ice Vending Capacity

Peak Vends Per Hour\*

Number of Vends Per Hour from Full Bin + Recovery = Total Vends

Model Number	Bin Storage lb./kg.	1 Hour Recovery Cap lb./kg.	2 fl. oz.			4 fl. oz.			6 fl. oz.			8 fl. oz.		
			Bin	Recovery	Total Vends	Bin	Recovery	Total Vends	Bin	Recovery	Total Vends	Bin	Recovery	Total Vends
MDT4F12A	12/5	19/9	192	+ 302	= 494	96	+ 151	= 247	64	+ 101	= 165	48	+ 76	= 124

1 lb. apx. = 32 fl. oz.

\*Based on 70° Air and 50° Water Temperatures

MDT4F12 – TouchFree<sup>®</sup> Ice Machine / Dispenser


Scotsman Ice Systems · 775 Corporate Woods Parkway · Vernon Hills, IL 60061

1-800-SCOTSMAN

Fax: 847-913-9844

E-mail: [customer.relations@scotsman-ice.com](mailto:customer.relations@scotsman-ice.com)

[www.scotsman-ice.com](http://www.scotsman-ice.com)



## Specifications

Model Number	Condenser Unit	Storage Capacity lb/kg	Basic Electrical Volts/Hz/Phase	Max. Fuse Size or HACR Circuit Breaker (amps)	Circuit Wires	Min. Circuit Ampacity	Energy Consumption kWh/100 lb (45.4 kg) 90°F(32°C)/70°F(21°C)	Water Usage Gallons/100 lb (liters/45.4 kg)	
								Potable 90°F(32°C)/70°F(21°C)	Condenser 90°F(32°C)/70°F(21°C)
MDT4F12A-1	Air	12/5	115/60/1	20	2	15.1	5.6	12/45.5	-

All units are stainless steel. Not designed for outdoor installations.

Refrigerant: R-134a

## All Models

Dimensions (W x D x H):

Unit:

14" x 23.75" x 34.31"  
(35.6 x 60.3 x 87.1 cm)

Shipping Carton:

17" x 26" x 39.75"  
(43.2 x 66 x 101 cm)

Shipping Weight:

155 lb / 70 kg

## Accessories

Model Number	Description
KWB4	Wall Mounting Kit for MDT3F12, MDT4F12
KPC-MDT	Portion Control Kit for MDT3, MDT4, MDT5 & MDT6
KTPS-MDT	Tamper Proof Screw Kit (including tool) to convert 1 MDT Dispenser

\* Scotsman recommends all ice machines have water filtration. See Scotsman Sanitation Matrix for details.

## Operating Requirements

	Minimum	Maximum
Air Temperatures	50°F (10°C)	100°F (38°C)
Water Temperatures	40°F (4.4°C)	100°F (38°C)
Remote Cond. Temps	-20°F (-29°C)	120°F (49°C)
Water Pressures	20 PSIG (1.4 bar)	80 PSIG (5.5 bar)
Electrical Voltage	-5%	+10%

Specifications and design are subject to change without notice.

Scotsman Ice Systems · 775 Corporate Woods Parkway · Vernon Hills, IL 60061

1-800-SCOTSMAN

Fax: 847-913-9844

E-mail: customer.relations@scotsman-ice.com

www.scotsman-ice.com

© 2012 Scotsman Ice Systems.

SIS-SS-DIS-MDT4F12 06-12